

A sport bicycle of classic proportions. A superior Trek-built Reynolds frame is equipped with a complete Campagnolo gruppo. The new Campy Triomphe design features clean aerodynamic styling with traditionally superior performance. Add plenty of efficient braze-ons like shift-lever bosses, double bottle mounts, and head-tube pump peg and you've got American innovation with an Italian accent.



Investment-cast bottom-bracket with low-friction cable routing



510

FRAME:

Main Tubes: Reynolds 501 Chromalloy Double Butted

Fork: Tange Mangalloy w/CCL Crown

Stays: True Temper Chromoly
Headset: Campagnolo Triomphe
B.B. Shell: Trek Cast w/Cable Guides
Headlug: Trek One-Piece Cast
Seat Lug: Trek Invest. Cast
Drop-Outs: Trek Cast w/Adjustors
Special Braze-ons: Top Tube Cable Guides, Dual Water Bottle Mounts, Chain Hanger, Shift Lever Bosses

Frame Sizes: 19" 21" 22.5" 24" 25.5"
Color: Black

COMPONENTS:

Crank: Campagnolo Triomphe Forged Alloy 52/40
Derailleurs: Campagnolo Triomphe Corsa
Shift Levers: Campagnolo Triomphe Braze-on

Freewheel: SunTour PS 6000 13-24 6-spd. Silver

Chain: Sedisport Silver

Brakes: Campagnolo Triomphe w/Hooded Levers

Pedals: Campagnolo Triomphe Alloy

Bar: Bellini Engraved Alloy

Stem: SR CT Aero Alloy

Hubs: Campagnolo Triomphe Q/R Alloy

Rims: Rigida 13-20 700C Alloy

Tires: Trek 700x25c

Seat Post: Campagnolo Triomphe Aero Forged Alloy

Saddle: San Marco Leather Sport
Extras: Campagnolo Triomphe Toe Clips and Straps, Alloy Water Bottle Cage w/Bottle

FRAME GEOMETRY FOR MODELS 400, 410, 420, 510, 520

	A	B	C	D	E	F	G	H
FRAME SIZE	SEAT TUBE length	SEAT TUBE angle	HEAD TUBE angle	TOP TUBE length	CHAIN STAY length	FORK OFFSET	DROP	WHEEL BASE
19"	47.5	73.5°	72.0°	53.6	42.5	4.5	7.2	99.4
21"	52.1	73.5°	72.0°	55.0	42.5	4.5	7.2	101.1
22.5"	55.9	73.5°	73.0°	56.0	42.5	4.5	7.2	102.0
24"	59.6	73.5°	73.0°	57.5	42.5	4.5	7.2	103.4
25.5"	63.5	73.5°	73.0°	58.5	42.5	4.5	7.2	105.0

FRAME GEOMETRY FOR MODEL 500

19"	47.5	73.5°	72.0°	53.6	42.5	3.8	7.2	98.7
21"	52.1	73.5°	72.0°	55.0	42.5	3.8	7.2	100.4
22.5"	55.9	73.5°	73.0°	56.0	42.5	3.8	7.2	101.3
24"	59.6	73.5°	73.0°	57.5	42.5	3.8	7.2	102.7
25.5"	63.5	73.5°	73.0°	58.5	42.5	3.8	7.2	104.3

FRAME GEOMETRY FOR MODEL 600

19"	47.5	73.5°	72.0°	53.6	42.5	3.8	7.2	98.7
21"	52.1	73.5°	72.0°	55.0	42.5	3.8	7.2	100.4
22.5"	55.9	73.5°	73.0°	56.0	42.5	3.8	7.2	101.3
24"	59.6	73.5°	73.0°	57.5	42.5	3.8	7.2	102.7
25.5"	63.5	73.5°	73.0°	58.5	42.5	3.8	7.2	104.3

All dimensions are in centimeters, unless otherwise stated.

